

Veedol Prima Super Tractor Oil Universal 10W-30

Material no. 03209P601

DESCRIPTION

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors. This oil gives the following benefits:

- Anti-wear and oxidation stability: proven protection of critical parts.
- Cold start: excellent fluidity at low temperature.

APPLICATION

This STOU* is advised for the lubrication of turbo-charged and uncharged diesel engines as well as 4-stroke gasoline engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-road equipment.

* Super Tractor Oil Universal

PERFORMANCE SPECIFICATIONS

API CG-4/GL-4/GL-5 (Low speed/high torque)/SF/CE ACEA E3
DIN 51524 T3 HVLPD

Veedol recommends for

Allison C4 (Agriculture applic.)
Case MAT 3525/MAT 3526
Ford ESN M2C134 C/D, ESN M2C159 B/C, FNH 82009201
JD J20C/J27
MF M 1135/1139/1143/1144/1145
NH 030C/410B/420A

ZF TE-ML 03A/05K/06A/06B/06C/07B/07D

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.860
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	75
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.4
Viscosity index, ASTM D2270	144
Pour point, ASTM, D6892 °C	-36
CCS viscosity at -25°C, ASTM D5293, mPa.s	6700
Flash Point COC, ASTM D92, °C	216

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.