

## **Veedol STOU 10W-40**

Material no. 03209P602

#### **DESCRIPTION**

**Veedol STOU 10W-40** is a modern multi-purpose oil for agricultural tractors and off-road vehicles, based on select solvent-refined base oils and special additives. This oil gives the following benefits:

- Very high dispersion and detergent capacity
- Excellent protection against wear, corrosion and foaming
- High oxidation resistance
- Excellent high-pressure characteristics
- High and stable viscosity index

### **APPLICATION**

This STOU\* has been developed in order to cover the following applications with a single oil:

- Motor oil for gasoline engines
- · Motor oil for suction and turbo-charged diesel engines
- Transmission oil (including wet brakes)
- Hydraulic oil

It is optimised for agricultural tractors and off-road equipment

\* Super Tractor Oil Universal

# PERFORMANCE SPECIFICATIONS

API GL-4/CG-4/GL-5 (Low speed/high torque)/SF/CE ACEA E3
DIN 51524 T3 HVLPD

### Veedol recommends for

Allison C4 (Agriculture applic.)

Case Mat 3525/3526

Ford ESN M2C-159B/C, ESN M2C134 C/D, FNH 82009203

JD J27/J20C

MF M 1145/M 1135/M 1139/M 1143/M 1144

NH 024C/NH 410B/NH 420A

ZF TE-ML 03A/05K/06A/06B/06C/07B/07D

# TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.868
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	88.2
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	13.8
Viscosity index, ASTM D2270	160
Pour point, ASTM, D6892 °C	-36
CCS viscosity at -25°C, ASTM D5293, mPa.s	6700
Flash Point COC, ASTM D92, °C	220

Version 2020-04

#### Veedol Deutschland GmbH

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.