

Veedol Racing Plus 4T 10W40

Material no. 03206P352

DESCRIPTION

Veedol Racing Plus 4T 10W-40 is a new generation semi-synthetic engine oil for four-stroke motorcycles formulated with high quality mineral and synthetic base oils combined with specially developed and balanced additives to give the following benefits:

- · Outstanding engine cleanliness
- Good cold start properties
- Optimal friction characteristics
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion

APPLICATION

This oil is specially developed for the lubrication of four-stroke motorcycles, and actively prevents sliding, sticking and/or rough changing of the clutch-plates.

PERFORMANCE SPECIFICATIONS

API SL Jaso MA2

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.851
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	90
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	14
Viscosity index, ASTM D2270	160
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	6.1
Pour point, ASTM, D6892 °C	-36
Colour, VISUAL	BROWN
CCS viscosity at -25°C, ASTM D5293, mPa.s	4900

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com