

Veedol EP Gear Oil 80W-90

Material no. 03203M207

DESCRIPTION	 Veedol Ep Gear Oil 80W-90 is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP additives to give the following properties: Good resistance to oxidation Good rust prevention, corrosion and foam inhibition Low pour point Good Extreme Pressure (EP) properties 	
APPLICATION	This multi purpose gear oil may be used in hypoid differentials, gearboxes and other transmissions for which a GL-4 EP transmission oil is advised.	
PERFORMANCE SPECIFICATIONS	API GL-4 Mil-L-2105	
TYPICAL CHARACTERISTICS	Density at 15°C, ASTM D4052, g/ml Kinematic viscosity at 40°C ASTM D445, mm²/s Kinematic viscosity at 100°C ASTM D445, mm²/s Viscosity index ASTM D2270 Pour point, ASTM D6892, °C Copper corrosion, ASTM D130 Flash Point COC, ASTM D92, °C	892 148 14.7 98 -30 1A 224

Version 12/08/2023

Veedol Deutschland GmbH

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.