

Veedol Hypoid Gear Oil 80W-90

Material no. 03203M213

DESCRIPTION

Veedol Hypoid Gear Oil 80W-90 is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP additives to give the following benefits:

- Long transmission life
- Excellent resistance to oxidation
- Very high activity against wear, corrosion and foaming
- Very good EP properties

APPLICATION

This gear oil is used in hypoid differentials under very heavy duty conditions and may be used in all transmissions that require heavy duty EP transmission oils.

PERFORMANCE SPECIFICATIONS

API GL-5 MIL-L-2105 C/D

Veedol recommends for

MAN 342 M-1/342 M-2

ZF TE-ML 05A/07A/12E/16B/16C/17B/19B

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.896
Kinematic viscosity at 40°C ASTM D445, mm ² /s	147
Kinematic viscosity at 100°C ASTM D445, mm ² /s	14.7
Viscosity index ASTM D2270	99
Pour point, ASTM D6892, °C	-33
Brookfield viscosity at -26°C, ASTM D2983, mPa.s	120000
Flash Point COC, ASTM D92, °C	210

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com