

### **Veedol Gear Oil Special HD 75W90**

Material no. 03203P201

### **DESCRIPTION**

**Veedol Gear Oil Special HD 75W-90** is a full-synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP additives to give the following benefits:

- Good clutch-switch performance at low temperatures
- Excellent resistance to oxidation
- Very high activity against wear, corrosion and foam
- Low pour point
- Very good EP properties
- Fuel economy

### **APPLICATION**

This gear oil is specifically formulated for gearboxes with integrated differentials of front-wheel driven cars.

## PERFORMANCE SPECIFICATIONS

API GL-4 + Ford WSD M2C200-C MIL-L-2105

#### Veedol recommends for

BMW MTF LT-4 VW 501 50

# TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.846
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	71
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	14
Viscosity index, ASTM D2270	206
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	110000
Flash Point COC, ASTM D92, °C	200

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39

Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.