

Veedol Sintron Ultra 0W30

Material no. 03201T001

DESCRIPTION

Veedol Sintron Ultra 0W-30 is a sophisticated full-synthetic fuel economy universal motor oil produced with high quality synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to give the following benefits:

- Lower fuel consumption
- High resistance to shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Very good detergency and dispersion
- · Very strong protection against wear, corrosion and foaming

APPLICATION

This universal, fuel economy synthetic motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated. It is not suitable for diesel particulate filters (DPF).

PERFORMANCE SPECIFICATIONS

ACEA A3/B4 API SM

Veedol recommends for

MB 229.3 BMW Longlife-01 VW 50200/50500

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052 g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	66.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.9
Viscosity index, ASTM D2270	179
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-51
Sulfated Ash, ASTM D874, Mass %	1.1
Flash Point COC, ASTM D92, °C	220
CCS viscosity at -35°C, ASTM D5293, mPa.s	5600

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com