

## **Veedol Sintron C1 5W30**

Material no. 03201T005

DESCRIPTION	<ul> <li>Veedol Sintron C1 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology and based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated. It gives the following benefits:</li> <li>Lower fuel consumption</li> <li>Suitable for modern catalysts</li> <li>Low combustion ash buildup (low SAPS)</li> <li>Fast cold start</li> <li>Safe lubrication film at high temperatures</li> <li>Very good detergency and dispersion</li> <li>Very strong protection against wear, corrosion and foaming</li> </ul>
APPLICATION	<ul> <li>Veedol Sintron C1 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be used in vehicles with modern three way catalysts and diesel particulate filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particulate filters for diesel engines</li> <li>Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.</li> </ul>
PERFORMANCE SPECIFICATIONS	ACEA C1/C2 Ford WSS-M2C934-B <b>Veedol recommends for</b> Jaguar Land Rover: STJLR.03.5005 Jaso DL-1
TYPICAL CHARACTERISTICS	Density at 15°C, ASTM D4052, g/ml0.852Kinematic viscosity at 40°C, ASTM D445, mm²/s59.1Kinematic viscosity at 100°C, ASTM D445, mm²/s10.5Viscosity index, ASTM D2270169B.N. (HCLO4 method), ASTM D2896, mg KOH/g6.4Pour point, ASTM D6892, °C-45CCS viscosity at -30°C, ASTM D5293, mPa.s5600Sulfated Ash, ASTM D874, Mass %0.5Flash Point COC, ASTM D92, °C224

Version 11/08/2023

Veedol Deutschland GmbH

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.