

Veedol Sintron C3 5W30 RN

Material no. 03201T006

DESCRIPTION	Veedol Sintron C3 5W30 RN can be used in systems with or without exhaust gas aftertreat- ment where C3 engine oils are required. Furthermore, this engine oil has the official Renault RN 17 approval. This means also that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.	
APPLICATION	 Broad coverage: reduced lubricant costs. Significant friction reduction: improved fuel efficiency and lowered emissions. Excellent engine cleanliness: outstanding engine protection during the entire oil drain interval. 	
PERFORMANCE SPECIFICATIONS	ACEA C3 Veedol recommends for Renault RN17	
TYPICAL CHARACTERISTICS	Density at 15°C, ASTM D4052, g/ml Kinematic viscosity at 40°C, ASTM D445, mm²/s Kinematic viscosity at 100°C, ASTM D445, mm²/s Viscosity index, ASTM D2270 B.N. (HCLO4 method), ASTM D2896, mg KOH/g Pour point, ASTM D6892, °C Sulfated Ash, ASTM D874, Mass % Flash Point COC, ASTM D92, °C	0.849 60.3 11.8 197 8.0 -39 0.78 226

Version 11/08/2023

Veedol Deutschland GmbH

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.