

Veedol Sintron C5 0W20 RFE

Material no. 03201T038

DESCRIPTION

Veedol Sintron C5 0W20 RFE is especially formulated for use in the newest Renault diesel engines with DPF which require an oil according to the new fuel economy specification RN17 FE of Renault, which is only suitable for engines adapted for the purpose of lower fuel consumption. Furthermore it can be used in all engines requiring the new ACEA low SAPS specification C5, which has more fuel economy potential than ACEA C3.

APPLICATION

- Fuel economy: superior fuel economy and CO₂ reduction.
- Superb shear stability performance: optimal contribution to high temperature viscosity
- Cold start: excellent low temperature performance

PERFORMANCE SPECIFICATIONS

ACEA C5

Veedol recommends for

Renault RN17 FE

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.840
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	38.5
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.2
Viscosity index, ASTM D2270	195
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C	-48
Sulfated Ash, ASTM D874, Mass %	0.79

Version 11/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39

Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, sepcially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.