

Veedol Sintron V 0W20

Material no. 03201T019

DESCRIPTION

Veedol Sintron V 0W-20 is a fuel economy SAE 0W20 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to give the following benefits:

- High fuel economy
- Good resistance to shearing
- Very fast cold start, even at very low temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

PERFORMANCE SPECIFICATIONS

ACEA A1/B1 ACEA C5 API SN

Approval

Volvo VCC RBS0-2AE

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.845
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	47.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.0
Viscosity index, ASTM D2270	172
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C -	-48
Sulfated Ash, ASTM D874, Mass %	0.8
Flash Point COC, ASTM D92, °C	224

Version 21/08/2023

Hans-Böckler-Straße 10 40764 Langenfeld, Germany Tel.: +49 (0) 2173 893 30-30 Fax: +49 (0) 2173 893 30-39 Mail: info@veedol.com The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and developement, the information contained herein is subject to changes without notification.