

Veedol Sintron F 0W30

Material no. 03201T025

DESCRIPTION

Veedol Sintron F 0W-30 is a full synthetic lubricant based on carefully selected base oils, mandatory for the EURO 6 TDCI Duratorq engines of the most recent Ford models (2014 onwards) with exhaust after treatment and turbocharger. The high-tech VI-improver in the oil provides high stability to ensure long oil drain intervals. It also allows the use of biofuels. It gives the following benefits:

- Total engine protection: keeps the engine clean
- Fuel economy: superior fuel economy and CO₂ reduction
- Cold start: excellent fluidity at low temperature

APPLICATION

Veedol Sintron F 0W-30 is developed for mandatory use in the newest EURO 6 TDCI Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W/30 viscosity grade and the ACEA C2 performance, thus providing a multi vehicle oil application. It has an optimised formulation for the latest car engines with exceptional fuel economy and extended service intervals.

PERFORMANCE SPECIFICATIONS

ACEA C2
Ford WSS-M2C950-A

Veedol recommends for
Jaguar Land Rover STJLR.03.5007

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	48.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.6
Viscosity index, ASTM D2270	187
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.0
Pour point, ASTM D6892, °C	-42
Sulfated Ash, ASTM D874, Mass %	0.79
Flash Point COC, ASTM D92, °C	210
CCS viscosity at -35°C, ASTM D5293, mPa.s	5600