

Veedol Sintron C5 0W20

Material no. 03201T038

DESCRIPTION

This full synthetic engine oil is specifically developed to meet the Opel OV0401547 specification. The ultralow viscosity grade of this lubricant enables the latest engine designs to reach their predetermined fueleconomy goals. In addition to this, the engine oil forms a powerful layer that absorbs harmful particulates and keeps the engine clean and protected.

- Fuel economy: superior fuel economy and CO2 reduction.
- Cold start: excellent fluidity at low temperature.
- Aftertreatment protection: full aftertreatment device protection.

APPLICATION

This engine oil offers complete protection to a range of modern passenger car and light truck diesel and gasoline engines, equipped with or without emission aftertreatment system. Furthermore, it can be used in combination with the latest fuel types, such as biofuels and ethanol-based fuels. The API SN Plus specification shows the lubricant's compatibility with highly fuel-efficient GDI engines, in which this oil prevents LSPI from damaging the engine components. This engine oil enables some of the most advanced engine designs to reach their targeted fuel-economy levels, which is proven by meeting the MB 229.71 and BMW Longlife-17FE+ specifications.

PERFORMANCE SPECIFICATIONS

ACEA C5
API SN/RC/SN Plus
Ilsac: GF-5

Approval
MB-Approval 229.71

Veedol recommends for

BMW Longlife-17FE+
GM dexosDTM
Jaguar Land Rover: STJLR.51.5122
Opel OV0401547
Volvo VCC RBS0-2AE

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.845
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	40.64
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.06
Viscosity index, ASTM D2270	176
B.N. (HClO4 method), ASTM D2896, mg KOH/g	7.7
Pour point, ASTM D6892, °C	-57
Sulfated Ash, ASTM D874, Mass %	0.6
Flash Point COC, ASTM D92, °C	210