

Veedol Transmission Synthetic 75W-90

Material no. 03203T216

DESCRIPTION

Veedol Transmission Synthetic 75W-90 is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials. This transmission oil gives the following benefits:

- Excellent frictional properties: very smooth gear shifting, no vibration
- Anti-wear and oxidation stability: superior protection of critical parts
- Extended oil life: excellent thermal and oxidation stability

APPLICATION

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.) of trucks and four-wheel drive vehicles.

PERFORMANCE SPECIFICATIONS

| | | |
|----------------------------------|--|--|
| API GL-5/GL-4/MT-1 SAE J 2360 | Veedol recommends for Arvin Meritor 0-76-N DAF GL5/MIL-PRF-2105E Iveco MIL-PRF-2105E MACK GO-J MAN 341 Z-2/342 M-3/341 E-3 MB 235.8 | MIL PRF-2105E Renault B0032/3 Annex 3 Scania STO 1 Volvo 97312 ZF TE-ML 05B/07A/08/ 12B/12L/12N/16F/17B/ 19C/21B |
|----------------------------------|--|--|

TYPICAL CHARACTERISTICS

| | |
|---|--------|
| Density at 15°C, ASTM D4052, g/ml | 0.868 |
| Kinematic viscosity at 40°C, ASTM D445, mm ² /s | 76.3 |
| Kinematic viscosity at 100°C, ASTM D445, mm ² /s | 15.2 |
| Viscosity index, ASTM D2270 | 203 |
| Pour point, ASTM D6892, °C | -48 |
| CCS viscosity at -40°C, ASTM D5293, mPa.s | 45.000 |